

WEIGHING SCALES/BALANCES



Top-loading Balances IBL-1000 Series feature weighing capacities of 210 g, 310 g, 610 g, 1100 g and readabilities of 0.01 g. Some applications include weighing, counting, check weighing, weighing under unstable conditions, peek hold and percentage (%).

Iris top-loading balances are designed for routine weighing applications in your workplace, offering accuracy and repeatability during essential weighing applications in education, laboratory and, industrial sector. It delivers competitive performance at an economical price, featuring RS232 connectivity for easy communication, and a backlit display and a simple interface for uncomplicated operation, these balances are perfectly designed for your workplace.

Standard features include Basic functionality for routine weighing applications. Equipped with three essential weighing modes, RS232 connectivity for data transfer and storage and internal calibration (in selected models) making them ideal for routine weighing applications.

Designed for uncomplicated operation with easy-to-use display and interface Equipped with an easy-to-read, bright backlit display and a simple user interface, they are incredibly easy to operate, with almost no training required.

Smart design and durable construction Iris top pan balances have a small footprint which saves on benchtop space while providing a large weighing surface. They are durably constructed, and feature a stainless-steel pan to withstand day-to-day use in the workplace.

- Standard RS-232 connectivity for easy data transfer
- 3 essential weighing modes
- Easy-to-read, bright backlit display and a simple user interface
- LCD display for showing the active functions
- High Readability 0.01 g
- Fast stabilization and response time of 2 seconds
- 130 mm round weighing pan

Model	IBL-1100	IBL-1200	IBL-1300	IBL-1400
Capacity	210 g	310 g	610 g	1100 g
Repeatability	0.02 g			
Display	LCD			
Resolution	0.01 g			
Pan Dimension	130 mm			
Linearity	0.03 g			
Working Temperature	5 to 25°C			
Certification				
Interface	RS232C, RS485 optional			
Stabilization Time	2 seconds			
Packing Dimension	310x230x130 mm			
Gross Weight	22 kg			
Electrical Requirement				
Catalogue No.	6809005-04	6809010-04	6809015-04	6809020-04

