



WATER/ WASTE WATER TESTING



cs@irisanalytical.com



+1 706 760 4500



www.irisanalytical.com

Portable Conductivity Meter ICM-200 Series provides the ideal solution for measuring TDS, DO, pH, pX, temperature, Salinity, DO Saturation all these parameters. The Conductivity meter is best for observing different applications such as the number of salts or dissolved solids in water. The readings are mechanically temperature compensated with the range of -5 to 135°C, delivers accurate reading over the entire range and manual temperature calibration to correct temperature deviation. CE Certified. Designed to increase productivity in the lab and in the field.

1. Conductivity / TDS / Salinity / Resistivity Mode: 6 point conductivity meter calibration with automatic temperature compensation ranging COND:0.0 to 100.0°C; salinity: 0 to 50 g/L. Support selectable ion such as H⁺, Ag⁺, Na⁺, K⁺, Cl⁻, F⁻ etc. Standard configuration including platinum black conductivity electrode, DO probe and standard buffer.
2. pH Mode: High accuracy portable multiparameter water quality meter is equipped with a large backlit LCD display. 1 to 5 points pH calibration with auto-buffer recognition with automatic temperature compensation ranging from pH: 0.0 to 100.0°C Standard configuration including pH combination electrode. Selectable automatic identification of 25 kinds of buffer solutions, including DIN and NIST. The automatic electrode slope display helps users decide whether to replace the sensor.
3. DO Mode: With automatic temperature compensation ranging from 0.0 to 40.0°C. Air-saturated water and zero oxygen solution.

Features

- Functional measuring parameters including conductivity, dissolve oxygen, pH, pX, and temperature
- Simple calibration 0 offset and Full scale
- Large, well-structured 7-inch touch screen and LCD display with navigation
- CE Certified
- Available in a portable model
- Automatic and manual temperature compensation
- Maximum storage: 2200 set
- Platinum black conductivity electrode; pH combination electrode, DO probe; standard buffer as standard configuration
- Compiled with USB and RS232 to connect with PC and Printer
- Li-on Battery

Accessories

- Platinum Black Conductivity Electrode;
- pH Combination Electrode;
- DO Probe (waterproof);
- Standard Buffer

