

PUMPS & ASPIRATORS

cs@irisanalytical.com

+1 706 760 4500

www.irisanalytical.com

Standard Peristaltic Pump is available with 5 series and 43 models and equipped with the LED display controller that permits monitoring of parameters and changes of speed. Appropriate for university laboratory, supporting ion chromatography and titrator, industrial sites, simple dispense, university laboratory and research institute, cement grinding aids, matching with an analytical instrument. Significant factors are set quickly and easily using the control panel on the housing; the speed can be programmed directly on the unit. Structures with ABS plastic and stainless steel housing.

Basic Peristaltic Pump ISPP-1000 Series are suitable for university laboratory, supporting ion chromatography and titrator. Run multichannel pumping with accurate flow control also features ABS plastic housing and servo motor, 3 Digital LED display with 4 pump drive and 2 different speeds range from 0.1 rpm when speed is 0 to 100, 1 rpm when speed is 100 to 600. Significant factors are set quickly and easily using the control panel on the housing; the speed can be programmed directly on the unit.

Precision Peristaltic Pump ISPP-2000 Series is suitable for industrial application, transfer liquid with large flow and high precision. Run multichannel pumping with accurate flow control also features ABS plastic housing and servo motor as well as a stepper motor, 3 Digital LED display with 4 pump drive and 2 different speeds range from 0.1 rpm when speed is 0 to 100, 1 rpm when speed is 100 to 600. Significant factors are set quickly and easily using the control panel on the housing; the speed can be programmed directly on the unit.

Standard Peristaltic Pump ISPP-3000 Series are basically used in simple dispense, university laboratory and research institute, matching with analytical instruments. Run multichannel pumping with accurate flow control also features with plastic-coated metal housing and servo motor as well as a stepper motor, LED display with 4 pump drive and 2 different speeds to range from 0.1 rpm when speed is 0 to 100, 1 rpm when speed is 100 to 600. Significant factors are set quickly and easily using the control panel on the housing; the speed can be programmed directly on the unit.

Laboratory Peristaltic Pump ISPP-4000 Series are used in cement grinding aids, support the industrial production line. Run multichannel pumping with accurate flow control also features with plastic-coated metal housing and servo motor as well as a stepper motor, LED display with 4 pump drive and 2 different speeds to range from 0.1 rpm when speed is 0 to 100, 1 rpm when speed is 100 to 600. Significant factors are set quickly and easily using the control panel on the housing; the speed can be programmed directly on the unit.

Basic Peristaltic Pump ISPP-1000 Series

Basic Peristaltic Pump ISPP-1050S

Basic Peristaltic Pump ISPP-1050S has 0.000829 to 570 ml/min flow rates and excellent dosing that used for timer function of simple dispensing function along with RS232 standard interface along with optional RS485 Modbus interface communicator.



- Support RS232 and RS485, the pump can be connected with PC to reach dispensing and filling function
- 3 Digital LED display the current speed
- ABS plastic constructing material
- A quick exchange of pump heads without the use of tools
- The strong, powerful, regulated drive unit
- Allow stacking of 4 pumps head for same drive, creating multichannel pump system
- Easy installation and low maintenance condition
- Materials have good rigidity and high precision
- Mechanical keypad to control the start/stop, speed, and direction

Basic Peristaltic Pump ISPP-1250S

Basic Peristaltic Pump ISPP-1250S has 0.000829 to 2280 ml/min flow rates and excellent dosing that used for timer function of simple dispensing function along with RS232 standard interface along with optional RS485 Modbus interface communicator.



- Support RS232 and RS485, the pump can be connected with PC to reach dispensing and filling function
- 3 Digital LED display the current speed
- ABS plastic constructing material
- A quick exchange of pump heads without the use of tools
- The strong, powerful, regulated drive unit
- Allow stacking of 4 pumps head for same drive, creating multichannel pump system
- Easy installation and low maintenance condition
- Materials have good rigidity and high precision
- Mechanical keypad to control the start/stop, speed, and direction

Basic Peristaltic Pump ISPP-1450S

Basic Peristaltic Pump ISPP-1450S has 0.000829 to 2280 ml/min flow rates and excellent dosing that used for timer function of simple dispensing function along with RS232 standard interface along with optional RS485 Modbus interface communicator.



- Support RS232 and RS485, the pump can be connected with PC to reach dispensing and filling function
- 3 Digital LED display the current speed
- ABS plastic constructing material
- A quick exchange of pump heads without the use of tools
- The strong, powerful, regulated drive unit
- Allow stacking of 4 pumps head for same drive, creating multichannel pump system
- Easy installation and low maintenance condition
- Materials have good rigidity and high precision
- Mechanical keypad to control the start/stop, speed, and direction

Precision Peristaltic Pump ISPP-2000 Series

Precision Peristaltic Pump ISPP-2000 Series is suitable for industrial application, transfer liquid with large flow and high precision. Run multichannel pumping with accurate flow control also features ABS plastic housing and servo motor as well as a stepper motor, 3 Digital LED display with 4 pump drive and 2 different speeds range from 0.1 rpm when speed is 0 to 100, 1 rpm when speed is 100 to 600. Significant factors are set quickly and easily using the control panel on the housing; the speed can be programmed directly on the unit.



Precision Peristaltic Pump ISPP-2341-12L has 0.00069 to 12 L/min flow rates and excellent dosing that used for timer function of simple dispensing function along with RS232 standard interface along with optional RS485 Modbus interface communicator.

Precision Peristaltic Pump ISPP-2590-6L has 0.3 to 6000 ml/min flow rates and excellent dosing that used for the timer function of simple dispensing function along with RS232 standard interface along with optional RS485 Modbus interface communicator.

Precision Peristaltic Pump ISPP-2918-3L has 0.211 to 3600 ml/min flow rates and excellent dosing that used for timer function of simple dispensing function along with RS232 standard interface along with optional RS485 Modbus interface communicator.

- Support RS232 and RS485, the pump can be connected with PC to reach dispensing and filling function
- 3 Digital LED display the current speed
- ABS plastic constructing material
- A quick exchange of pump heads without the use of tools
- The strong, powerful, regulated drive unit
- Allow stacking of 4 pumps head for same drive, creating multichannel pump system
- Easy installation and low maintenance condition
- Materials have good rigidity and high precision
- Mechanical keypad to control the start/stop, speed, and direction

Standard Peristaltic Pump ISPP-3000 Series



Standard Peristaltic Pump ISPP-3000 Series are basically used in simple dispense, university laboratory and research institute, matching with analytical instruments. Run multichannel pumping with accurate flow control also features with plastic-coated metal housing and servo motor as well as a stepper motor, LED display with 4 pump drive and 2 different speeds to range from 0.1 rpm when speed is 0 to 100, 1 rpm when speed is 100 to 600. Significant factors are set quickly and easily using the control panel on the housing; the speed can be programmed directly on the unit.

Standard Peristaltic Pump ISPP-3444P has 0.000829 to 570 ml/min flow rates and excellent dosing that used for timer function of simple dispensing function along with 8 modes of external control of RS232 standard interface along with optional RS485 Modbus interface communicator.

Standard Peristaltic Pump ISPP-3666P has 0.000829 to 1330 ml/min flow rates and excellent dosing that used for timer function of simple dispensing function along with 8 modes of external control of RS232 standard interface along with optional RS485 Modbus interface communicator.

Standard Peristaltic Pump ISPP-3888P has 0.000829 to 2280 ml/min flow rates and excellent dosing that used for the timer function of simple dispensing function along with 8 modes of external control of RS232 standard interface along with optional RS485 Modbus interface communicator.

Standard Peristaltic Pump ISPP-3444P

Standard Peristaltic Pump ISPP-3444P has 0.000829 to 570 ml/min flow rates and excellent dosing that used for timer function of simple dispensing function along with 8 modes of external control of RS232 standard interface along with optional RS485 Modbus interface communicator.



- Support RS232 and RS485, the pump can be connected with PC to reach dispensing and filling function
- LED display the current speed
- Plastic coated metal housing constructing material
- Mechanical keypad to control the start/stop, speed, and direction
- Negligible noise and vibration
- Design with ultra-quiet drive and precision control
- Testing time range 0.5 s to 999 s
- Left-right reversal
- Display lamp of external mode
- Equipped with timer for 60 seconds teat
- A quick exchange of pump heads without the use of tools

Standard Peristaltic Pump ISPP-3666P

Standard Peristaltic Pump ISPP-3666P has 0.000829 to 1330 ml/min flow rates and excellent dosing that used for timer function of simple dispensing function along with 8 modes of external control of RS232 standard interface along with optional RS485 Modbus interface communicator.



- Support RS232 and RS485, the pump can be connected with PC to reach dispensing and filling function
- LED display the current speed
- Plastic coated metal housing constructing material
- Mechanical keypad to control the start/stop, speed, and direction
- Negligible noise and vibration
- Design with ultra-quiet drive and precision control
- Testing time range 0.5 s to 999 s
- Left-right reversal
- Display lamp of external mode
- Equipped with timer for 60 seconds teat
- A quick exchange of pump heads without the use of tools

Standard Peristaltic Pump ISPP-3888P

Standard Peristaltic Pump ISPP-3888P has 0.000829 to 2280 ml/min flow rates and excellent dosing that used for the timer function of simple dispensing function along with 8 modes of external control of RS232 standard interface along with optional RS485 Modbus interface communicator.



- Support RS232 and RS485, the pump can be connected with PC to reach dispensing and filling function
- LED display the current speed
- Plastic coated metal housing constructing material
- Mechanical keypad to control the start/stop, speed, and direction
- Negligible noise and vibration
- Design with ultra-quiet drive and precision control
- Testing time range 0.5 s to 999 s
- Left-right reversal
- Display lamp of external mode
- Equipped with timer for 60 seconds teat
- A quick exchange of pump heads without the use of tools

Laboratory Peristaltic Pump ISPP-4000 Series

Laboratory Peristaltic Pump ISPP-4000 Series are used in cement grinding aids, support the industrial production line. Run multichannel pumping with accurate flow control also features with plastic-coated metal housing and servo motor as well as a stepper motor, LED display with 4 pump drive and 2 different speeds to range from 0.1 rpm when speed is 0 to 100, 1 rpm when speed is 100 to 600. Significant factors are set quickly and easily using the control panel on the housing; the speed can be programmed directly on the unit.



Laboratory Peristaltic Pump ISPP-4955 has 0.00166 to 570 ml/min flow rates and excellent dosing that used for the timer function of simple dispensing function along with 8 modes of external control of RS232 standard interface along with optional RS485 Modbus interface communicator.

Laboratory Peristaltic Pump ISPP-4551 has 0.00166 to 1330 ml/min flow rates and excellent dosing that used for the timer function of simple dispensing function along with 8 modes of external control of RS232 standard interface along with optional RS485 Modbus interface communicator.

Laboratory Peristaltic Pump ISPP-4089 has 0.00166 to 2280 ml/min flow rates and excellent dosing that used for the timer function of simple dispensing function along with 8 modes of external control of RS232 standard interface along with optional RS485 Modbus interface communicator.

Laboratory Peristaltic Pump ISPP-4955

Laboratory Peristaltic Pump ISPP-4955 has 0.00166 to 570 ml/min flow rates and excellent dosing that used for the timer function of simple dispensing function along with 8 modes of external control of RS232 standard interface along with optional RS485 Modbus interface communicator.



- Equipped with toggle switch control
- Support RS232 and RS485, the pump can be connected with PC to reach dispensing and filling function
- 3 Digital LED display the current speed
- Plastic coated constructing material
- A quick exchange of pump heads without the use of tools
- The strong, powerful, regulated drive unit
- Negligible noise and vibration
- Testing time range 0.5 s to 999 s
- Toggle switch and rotary encoded switch are used to control unit

Laboratory Peristaltic Pump ISPP-4551

Laboratory Peristaltic Pump ISPP-4551 has 0.00166 to 1330 ml/min flow rates and excellent dosing that used for the timer function of simple dispensing function along with 8 modes of external control of RS232 standard interface along with optional RS485 Modbus interface communicator.



- Equipped with toggle switch control
- Support RS232 and RS485, the pump can be connected with PC to reach dispensing and filling function
- 3 Digital LED display the current speed
- Plastic coated constructing material
- A quick exchange of pump heads without the use of tools
- The strong, powerful, regulated drive unit
- Negligible noise and vibration
- Testing time range 0.5 s to 999 s
- Toggle switch and rotary encoded switch are used to control unit

Laboratory Peristaltic Pump ISPP-4089

Laboratory Peristaltic Pump ISPP-4089 has 0.00166 to 2280 ml/min flow rates and excellent dosing that used for the timer function of simple dispensing function along with 8 modes of external control of RS232 standard interface along with optional RS485 Modbus interface communicator.



- Equipped with toggle switch control
- Support RS232 and RS485, the pump can be connected with PC to reach dispensing and filling function
- 3 Digital LED display the current speed
- Plastic coated constructing material
- A quick exchange of pump heads without the use of tools
- The strong, powerful, regulated drive unit
- Negligible noise and vibration
- Testing time range 0.5 s to 999 s
- Toggle switch and rotary encoded switch are used to control unit



IRIS Analytical Inc.

cs@irisanalytical.com +1 706 760 4500 www.irisanalytical.com