

PUMPS & ASPIRATORS

cs@irisanalytical.com

+1 706 760 4500

www.irisanalytical.com

Laboratory Peristaltic Pump ISPP-4000 Series are used in cement grinding aids, support the industrial production line. Run multichannel pumping with accurate flow control also features with plastic-coated metal housing and servo motor as well as a stepper motor, LED display with 4 pump drive and 2 different speeds to range from 0.1 rpm when speed is 0 to 100, 1 rpm when speed is 100 to 600. Significant factors are set quickly and easily using the control panel on the housing; the speed can be programmed directly on the unit.

Laboratory Peristaltic Pump ISPP-4955 has 0.00166 to 570 ml/min flow rates and excellent dosing that used for the timer function of simple dispensing function along with 8 modes of external control of RS232 standard interface along with optional RS485 Modbus interface communicator.

Laboratory Peristaltic Pump ISPP-4551 has 0.00166 to 1330 ml/min flow rates and excellent dosing that used for the timer function of simple dispensing function along with 8 modes of external control of RS232 standard interface along with optional RS485 Modbus interface communicator.

Laboratory Peristaltic Pump ISPP-4089 has 0.00166 to 2280 ml/min flow rates and excellent dosing that used for the timer function of simple dispensing function along with 8 modes of external control of RS232 standard interface along with optional RS485 Modbus interface communicator.

Laboratory Peristaltic Pump ISPP-4955

Laboratory Peristaltic Pump ISPP-4955 has 0.00166 to 570 ml/min flow rates and excellent dosing that used for the timer function of simple dispensing function along with 8 modes of external control of RS232 standard interface along with optional RS485 Modbus interface communicator.



- Equipped with toggle switch control
- Support RS232 and RS485, the pump can be connected with PC to reach dispensing and filling function
- 3 Digital LED display the current speed
- Plastic coated constructing material
- A quick exchange of pump heads without the use of tools
- The strong, powerful, regulated drive unit
- Negligible noise and vibration
- Testing time range 0.5 s to 999 s
- Toggle switch and rotary encoded switch are used to control unit

Laboratory Peristaltic Pump ISPP-4551

Laboratory Peristaltic Pump ISPP-4551 has 0.00166 to 1330 ml/min flow rates and excellent dosing that used for the timer function of simple dispensing function along with 8 modes of external control of RS232 standard interface along with optional RS485 Modbus interface communicator.



- Equipped with toggle switch control
- Support RS232 and RS485, the pump can be connected with PC to reach dispensing and filling function
- 3 Digital LED display the current speed
- Plastic coated constructing material
- A quick exchange of pump heads without the use of tools
- The strong, powerful, regulated drive unit
- Negligible noise and vibration
- Testing time range 0.5 s to 999 s
- Toggle switch and rotary encoded switch are used to control unit

Laboratory Peristaltic Pump ISPP-4089

Laboratory Peristaltic Pump ISPP-4089 has 0.00166 to 2280 ml/min flow rates and excellent dosing that used for the timer function of simple dispensing function along with 8 modes of external control of RS232 standard interface along with optional RS485 Modbus interface communicator.



- Equipped with toggle switch control
- Support RS232 and RS485, the pump can be connected with PC to reach dispensing and filling function
- 3 Digital LED display the current speed
- Plastic coated constructing material
- A quick exchange of pump heads without the use of tools
- The strong, powerful, regulated drive unit
- Negligible noise and vibration
- Testing time range 0.5 s to 999 s
- Toggle switch and rotary encoded switch are used to control unit



IRIS Analytical Inc.

cs@irisanalytical.com +1 706 760 4500 www.irisanalytical.com