Top-loading Balances IBL-2200S



Top-loading Balances IBL-2200S feature weighing capacities of 1100 g,and readabilities of 0.1 g. Some applications include weighing, counting, check weighing, weighing under unstable conditions, peek hold and percentage (%).

Iris top-loading balances are designed for routine weighing applications in your workplace, offering accuracy and repeatability during essential weighing applications in education, laboratory and, industrial sector. It delivers competitive performance at an economical price, featuring RS232 connectivity for easy communication, and a backlit display and a simple interface for uncomplicated operation, these balances are perfectly designed for your workplace.

Standard features include Basic functionality for routine weighing applications. Equipped with three essential weighing modes, RS232 connectivity for data transfer and storage and internal calibration (in selected models) making them ideal for routine weighing applications.

Designed for uncomplicated operation with easy-to-use display and interface Equipped with an easy-to-read, bright backlit display and a simple user interface, they are incredibly easy to operate, with almost no training required.

Smart design and durable construction Iris top pan balances have a small footprint which saves on benchtop space while providing a large weighing surface. They are durably constructed, and feature a stainless-steel pan to withstand day-to-day use in the workplace.

Technical Specification:

Model	IBL-2200S
Capacity	1100 g
Repeatability	0.2 g
Resolution	0.1 g
Display	LCD
Pan Dimensions	130 mm
Linearity	0.3 g
Working Temperature	5 to 25°C
Interface	RS232C, RS485 optional
Stabilization Time	2 seconds
Dimensions	310x230x130 mm
Net Weight	22 kg
Catalogue No.	68011510-04

Technical Data:

Model	IBL-2100S	IBL-2200S	IBL-2300S	IBL-2400S	IBL-2500S
Capacity	610 g	1100 g	2100 g	3100 g	5100 g
Repeatability	0.2 g				
Display	LCD				
Readability	0.1 g				
Pan Dimension	130 mm			160x160 mm	
Linearity	0.3 g				
Working Temperature	5 to 25°C				
Interface	RS232C, RS485 optional				
Stabilization Time	2 seconds				
Dimension	310x230x130 mm				
Weight	22 kg				
Catalogue No.	68011505-04	68011510-04	68011515-04	68011520-04	68011525-04



Iris Analytical Ltd.

66 W Flagler St #900 Miami, Florida 33130 United States