Top-loading Balances
IBL-6006S(110V)



Top-loading Balances IBL-6006S feature weighing capacities of 15 kg and readabilities of 0.1g. Some applications include weighing, counting, check weighing, weighing under unstable conditions, peek hold and percentage (%).

Iris top-loading balances are designed for routine weighing applications in your workplace, offering accuracy and repeatability during essential weighing applications in education, laboratory and, industrial sector. It delivers competitive performance at an economical price, featuring RS232 connectivity for easy communication, and a backlit display and a simple interface for uncomplicated operation, these balances are perfectly designed for your workplace.

Standard features include Basic functionality for routine weighing applications. Equipped with three essential weighing modes, RS232 connectivity for data transfer and storage and internal calibration (in selected models) making them ideal for routine weighing applications.

Designed for uncomplicated operation with easy-to-use display and interface Equipped with an easy-to-read, bright backlit display and a simple user interface, they are incredibly easy to operate, with almost no training required.

Smart design and durable construction Iris top pan balances have a small footprint which saves on benchtop space while providing a large weighing surface. They are durably constructed, and feature a stainless-steel pan to withstand day-to-day use in the workplace.

Technical Specification:

Model	IBL-6006S(110V)
Capacity	15 kg
Repeatability	0.1 g
Display	LCD
Pan Dimensions	255x190 mm
Functions	Unit Transforms, Counting, Percentage
Interface	RS232
Dimensions	350x290x160 mm
Net Weight	4 kg
Electrical Requirements	110V
Catalogue No.	6801352001

Technical Data:

Model	IBL-6001S		IBL-6002S		IBL-6004S		IBL-6006S		IBL-6008S		IBL-6010S	
Capacity	6000 g		8000 g		10 kg		15 kg		20 kg		30 kg	
Display	LCD											
Readability	0.1 g											
Pan Dimension	255x190 mm											
Function	Unit Transforms, Counting, Percentage											
Interface	RS232											
Packing Dimension	350x290x160 mm											
Gross Weight	4 kg											
Electrical Requirement	220V	110V	220V	110V	220V	110V	220V	110V	220V	110V	220V	110V
Catalogue No.	6801350502	6801350501	6801351002	6801351001	6801351502	6801351501	6801352002	6801352001	6801352502	6801352501	6801353002	6801353001



Iris Analytical Ltd.

66 W Flagler St #900 Miami, Florida 33130 United States