

Digital Autoclave/Steam Sterilizer IHA-5200



Digital Autoclave/Steam Sterilizer IHA-5200 basic 200L horizontal autoclave suitable for sterilizing heavy load and instruments for medical and laboratory use.

Comes with drying function, suitable dressing drying and features with automatic safety valve with inner pressure over 0.24 MPa and the steam exhausting to the water link. The machine has maximum sterilization pressure of 134°C with overload pressure protection. Built-in efficient steam generator, microcomputer temperature control, especially designed for bulk volume and highest flexibility in processing requirement.

Technical Specification:

Model	IHA-5200
Capacity (liters)	200L
Chamber Dimensions (mm)	515×1000 mm
Operating Temperature (°C)	134°C
Adjustment of Temperature	40 to 134°C
Working Pressure	0.22Mpa
Sterilisation Timer	0 to 99 min
Drying Time	0 to 99 min
External Dimensions (w x d x h) mm	1400×750×1700 mm
Net Weight (kg)	350 kg
Gross Weight (kg)	436kg
Shipping Dimensions (w x d x h) mm	1560×910×1880 mm
Power (W)	9000 W
Electrical Requirements	220V/50Hz
Catalogue No.	580901002

Technical Data:

Model	IHA-5100	IHA-5200	IHA-5300
Capacity	150L	200L	280L
Chamber Size	440×1000 mm	515×1000 mm	600×1000 mm
Materials	stainless steel		
Working Temperature	0.22 Mpa		
Working Pressure	134°C		
Temperature Adjustment	40°C - 134°C		
Sterilization Time Range	0-99 min		
Drying Time Range	0-99 min		
Heat Average	? ±1°C		
Display	Digital Display		
Certification			
Power Consumption	9KW	9KW	12KW
Dimension	1400×650×1600 mm	1400×750×1700 mm	1520×910×1900 mm
Packing Dimension	1560×820×1820 mm	1560×910×1880 mm	1680×1080×2100 mm
Net Weight	340 kg	350 kg	462 kg
Gross Weight	430 kg	436 kg	570 kg
Electrical Requirement	220V 50HZ		380V 50HZ
Catalogue No.	580900502	580901002	580901503



Iris Analytical Ltd.

66 W Flagler St #900 Miami, Florida 33130 United States