Portable Centrifuge IPC-130(220V/50Hz)



Portable Centrifuge IPC-130 s are ideal for the separation of serum plasma, urea, blood samples and other routine applications in hospital and research laboratories.

The IPC-130 are most powerful and competitive centrifuge in its class. it can be placed with 6 of 15ml conical tubes or glass tubes, 8 of 15ml conical tubes or glass tubes conical tubes which with screw caps The speed can be l00- 5000RPM. the LCD display with ability to change be between RPM and RCF.

Technical Specification:

Product Type	Portable Centrifuge
Model	IPC-130
Speed Range (rpm)	5000 rpm
Max RCF	3074xg
Capacity	5mlX12
Power	40W
Electrical Requirements	220V/50Hz
Catalogue No.	140201502

Technical Data:

Model	IPC-110		IPC-120		IPC-130	
Max. capacity	15mlX6		15mlX8		5mlX12	
Max. speed rpm (Angle rotor)	5000 rpm					
Speed increment	100 rpm					
Max. RCF[×g]	3074xg					
Noise level at max. speed(approximately)	?60dB(A)					
Max. Acceleration time	20-80 seconds					
Max. Deceleration time	20-80 seconds					
Power consumption drive	40W					
Electrical Requirements	110V/60Hz	220V/50Hz	110V/60Hz	220V/50Hz	110V/60Hz	220V/50Hz
Catalogue No.	140200501	140200502	140201001	140201002	140201501	140201502



Iris Analytical Ltd.

66 W Flagler St #900 Miami, Florida 33130 United States