Portable Centrifuge IPC-600(110V/60Hz)



Portable Centrifuge IPC-600 suitable for clinic, research and university application.Low speed, user friendly large LED display to display real time information and parameter. Spins samples volume up to 15mlx6 with maximum speed 4000 rpm and available with acceleration and for deceleration profile with high efficiency. Replacing and changing rotor by simply lift the rotor out of the shaft without breaking your back or damaging the centrifuge. Ideal for microfiltration and rapid spinning accelerates and decelerates within couples of minutes to ensure excellent consequences of sample separation

Technical Specification:

Product Type	Portable Centrifuge
Model	IPC-600
Speed Range (rpm)	4000 rpm
Max RCF	1980×g
Capacity	15mlx6
Timer	1 to 99min
External Dimemsions (HxLxW) mm	310×260×220 mm
Net Weight (kg)	14 kg
Shipping Dimensions (HxLxW) mm	370×320×280mm
Electrical Requirements	110V/60Hz
Catalogue No.	140450501

Technical Data:

Model	IPC-600	
Capacity	15mlx6	
Max RCF	1980×g	
Speed Range	4000 rpm	
Noise	<65dB(A)	
Revolution/rpm	±30 rpm	
Timer	1 to 99min	
Dimension	310×260×220 mm	
Packing Dimension	370×320×280mm	
Weight	14 kg	
Electrical Requirements	110V/60Hz	220V/50Hz
Catalogue No.	140450501	140450502



Iris Analytical Ltd.

66 W Flagler St #900 Miami, Florida 33130 United States