


Microcentrifuge IBMC-3015(220/60Hz)



Microcentrifuge IBMC-3015 is ISO9001, CE, and FDA certify programmable micro refrigerated centrifuge and ideal for collecting microorganisms, cell debris, cells, large organelles, sulphate precipitates, and immune deposits, etc. small footprint of capacity up to 36x1.5 ml/2.2ml with maximum speed ranging 16500 rpm. Microcomputer control, DC brushless motor. Features with LCD touch screen with multi-functional knob combination parameters. Available with 9 profiles for acceleration and for deceleration with high efficiency. For safety we introduced electronic door lock function and, imbalance detection, over-speed protection, inching function, short-spin function.

Accessories



Rotors

Model	IBMC-3015
Rotor	Rotor 1: 1.5/2.2ml x 12; 16500rpm; 18360 x g Rotor 2: 5ml x 12; 12000rpm; 10142 x g Rotor 3: 1.5/2.2ml x 24; 15000rpm; 21530 x g Rotor 4: 1.5/2.2ml x 36; 11000rpm; 10790 x g Rotor 5: 0.5ml x 48; 12000rpm; 10920 x g Rotor 6: 0.2ml x 8 x 3; 15000rpm; 13800 x g Rotor 7: 0.5ml x 18; 16000rpm; 15300 x g

Technical Specification:

Product Type	Micro Centrifuge
Model	IBMC-3015
Speed Range (rpm)	16500 rpm
Max RCF	21532×g
Capacity	36x1.5 ml/2.2ml
Display	LCD
Timer	1min to 99h, 59min
Certifications/Compliance	ISO9001, CE, and FDA
External Dimemsions (HxLxW) mm	280×540×300 mm
Net Weight (kg)	30 kg
Shipping Dimensions (HxLxW) mm	400×660×400 mm
Electrical Requirements	220/60Hz, 10A,
Catalogue No.	140600502

Technical Data:

Model	IBMC-3015	IBMC-3017
Capacity	36x1.5 ml/2.2ml	1.5ml/2.2ml×36
Max Speed	21532×g	21532×g
Max RCF	16500 rpm	17000 rpm
Revolution/rpm	± 30rpm	
Noise	<65dB(A)	
Time Setting	1min to 99h, 59min	
Certification	ISO9001, CE, and FDA	
Display	LCD	
Dimension	280×540×300 mm	
Packing Size	400×660×400 mm	480×670×585 mm
Weight	30 kg	
Electrical Requirement	AC110/50Hz, 10A,	220V/60Hz, 10A
Catalogue No.	140600501	140600502

Accessories:

Model	Image	Name	Details
140600501		Angle Rotor 1	1.5/2.2ml×12; 16500rpm;18360×g
140600501		Angle Rotor 2	5ml×12; 12000rpm;10142×g
140600501		Angle Rotor 3	1.5/2.2ml×24;15000rpm;21530×g
140600501		Angle Rotor 4	1.5/2.2ml×36; 11000rpm;10790×g
140600501		Angle Rotor 5	0.5ml×48; 12000rpm;10920×g
140600501		Angle Rotor 6	0.2ml×8×3;15000rpm;13800×g
140600501		Angle Rotor 7	0.5ml×18; 16000rpm;15300×g



Iris Analytical Ltd.

66 W Flagler St #900 Miami, Florida 33130 United States