

Microcentrifuge IBMC-4100



Microcentrifuge IBMC-4100 design with interchangeable rotors for procedure with 2×8×0.2 ml (PCR) strip tubes with adjustable timing and RPM during operation anytime, as well as to check centrifugal force without stopping the machine.

The IBMC-4100 use in different applications PCR laboratories, clinical research and molecular biology and general cell culture applications. For safety we introduced electronic door lock. Available different accessories which can accommodate different capacities rotors.

Technical Specification:

Product Type	Micro Centrifuge
Model	IBMC-4100
Speed Range (rpm)	6000 rpm
Max RCF	1248×g
Capacity	2x8x0.2 ml
Display	Digital Display
External Dimemsions (HxLxW) mm	230x190x170 mm
Net Weight (kg)	4.5 kg
Electrical Requirements	AC 220V 50/60Hz
Catalogue No.	140650502

Technical Data:

Model	IBMC-4100	IBMC-4200	IBMC-4300	IBMC-4400
Shaking Speed	6000 rpm	10000 rpm	12000 rpm	6000 rpm
RCF Speed	1248×g	6596×g	7567×g	2374×g
Rotors Capacity	2x8x0.2 ml	12x1.5/0.5/0.2 ml	6x1.5/0.5/0.2 ml	12x1.5 ml, 2x8x0.2 ml (PCR)
Display	Digital Display			
Noise	748Db			
Power Consumption	50 VA			
Dimension	230x190x170 mm			
Weight	4.5 kg			
Power	50VA			
Dimension	230x190x170 mm			
Weight	4.5 kg			
Electrical Requirement	AC 220V 50/60Hz			
Catalogue No.	140650502	140651002	140651502	140652002



Iris Analytical Ltd.

66 W Flagler St #900 Miami, Florida 33130 United States