Unstirred Water Bath WB-200



- Tank is using seamless stainless steel and outside body is powder painting
- Screen-touch panel, micro-computer PID digital display
- Overheat protector
- The water bath with circulator using electric heat tube to unify temperature inside
- The sensor is PT-100Ω
- Gable cover (AC-100) sold separately for your option.
- Heater of stainless steel

Technical Specification:

Model	WB-200
Capacity (liters)	20 L
Min. Temperature (℃)	Ambient +5℃
Max. Temperature (℃)	100℃
Temp. Accuracy (℃)	±0.1℃
Temperature Controller	PID Control
Temp. Display	LED Display
Inside Dimensions (WxDxH) mm	495 mm
Inside Dimension (Depth) mm	295 mm
Inside Dimension (Height) mm	150 mm
Overall Dimensions (WxDxH) mm	540 x 340 x 315 mm
Net Weight (kg)	12kg
Electrical Requirements	220V/50Hz

Technical Data:

Model	WB-100		WB-200	
Temperature Range	Ambient+5? ~ 100?			
Temp. Accuracy (?)	±0.1?			
Temp. Control	PIDControl			
Temp. Display (?)	LEDDisplay			
Volume (liters)	10 L		20 L	
Inside Dimension (WxDxH) mm	295 x 235 x 150 mm		495 x 295 x 150 mm	
Outside Dimension (WxDxH) mm	340 x 280 x 315 mm		540 x 340 x 315 mm	
Net Weight (kg)	8kg		12kg	
Gross Weight (kg)				
Electrical Requirements	110V/60Hz	220V/50Hz	110V/60Hz	220V/50Hz
Catalogue No.				



Iris Analytical Ltd.

66 W Flagler St #900 Miami, Florida 33130 United States